



Numerous sizes and custom options available.

DuraFiber™ Shelters

Super-Strong, Lightweight, Insulated

Shelter your equipment, electronics, and chemicals from extreme weather and temperatures with Orenco Composites' prefab DuraFiber™ Shelters — a uniquely rugged and affordable solution.

DuraFiber Shelters are made of fiberglass using a closed-molded (not sprayed up), single-piece construction process to ensure a leakproof, seamless structure. The insulated, foam-core fiberglass walls have a thickness of 2"-4" (50-100 mm).

Interior surfaces are protected with a polyester gelcoat, while exterior surfaces are protected with a high performance polyaspartic urethane.

The result? A super-strong, lightweight, insulated structure that is durable, corrosion-resistant, and easily transportable by truck, rail, cargo container, or aircraft. Numerous sizes and custom options are available.

See details on back.



DuraFiber™ Shelters

SHELTERS SERVE MANY INDUSTRIES

- Water & wastewater
- Telecommunications
- Transportation
- Mining, oil & gas

INDUSTRIAL APPLICATIONS

- Pump stations
- Motor control centers
- Power distribution centers
- Process & monitoring equipment
- Generator housing & sound attenuation
- Chem feed & storage



A Range of Standard and Custom Features:

Standard Features/Specifications

- Single-piece, closed-molded fiberglass construction
- Integral foam-core insulation in walls and roof
- Built-in internal pocket attachment system
- Fiberglass entry door
- Interior and exterior lighting
- Corrosion-resistant, UV-stable finish
- Light and transportable; lifting brackets for moving/setting
- Standard dimensions and specifications ...
 - Length: 4-20 ft, in 2-ft increments (1.2-6.1 m, 0.6-m)
 - Width: 4, 6, or 8 ft (1.2, 1.8, or 2.4 m)
 - Height: 8.0 ft (2.4 m)
 - R-12 to R-24 insulation value (RSI-2.1 to RSI-4.2)
 - 100 lb/ft² roof rating, live load (488 kg/m²)
 - 130 mph wind-rating (209 kph)

Optional Features

- Interior and exterior colors
- Interior and exterior lighting
- Anti-skid fiberglass floor, integrally bonded and sealed
- HVAC systems
- Electrical outlets

Custom Features

- Additional shelter widths and lengths
- Insulation values of R-24 or greater (RSI-4.2)
- Windows/interior walls
- Load centers, transformers, and control systems



Call **Orenco Composites** at **(800) 348-9843** for more information or to request a Specification Sheet.