Orenco has prepared these drawings for use by the design engineer. Orenco will not be responsible or liable for unauthorized changes to or uses of these drawings. All changes to these drawings must be made in writing and must be approved by the UNAUTHORIZED CHANGES & USES * 1,250 Gallons minimum capacity for 5 bedrooms 1,500 Gallons minimum capacity for 6 bedrooms. **AX25RT** Inlet Treatment System - Gravity Discharge * Primary Tank - Side View Primary Tank - Top View Slope to drain away from lid AdapterPRTA Tank Biotube® Effluent Filter— Model FTS0444-36V or Model FTW0444-36V or Model FT0822-14B PRODUCT CONFIGURATION DRAWINGS L.L.Orenco 24"Ø PVC Access Riser(s) with 24"Ø Gasketed Lid 0.21" (typ)-AX25 800 gal. Recirc. Tank - Side View AX25 800 gal. Recirc. Tank - Top View **Orenco Systems** Incorporated Changing the Way the World Does Wastewater ValveRecirc. Return Optional 1" Thick Insulation For Cold Weather Applications 102" Recirc. Final Discharge Transfer Line Pump Vault Recirc. Drawn For: Drawn By: BEN SMITH -Vent Splice Box Splice Box Recirc Pump Final Discharge High Level Alarm High Level Override Redundant Off / Low Level Alaym PumpOrenco Recirc. Project: System Discharge Chamber - End View Filter Tank Dry Weight: 950 lbs AX25RT Mode 1A 0 of Tank) (35" from Bottom Invert Liquid Level **Design and Installation Notes** Start-up And Service To Be Performed By An AdvanTex Trained Service Provider • Installation To Be Performed By An • For Expected Flows 6 Bedrooms or less **Control Panel Detail** AdvanTex Trained Installer Only **6** Discharge Detail Not To Scale Not To Scale 0 Sheet: Scale: 32.5" Exterior Invert (35" is Actual Invert of Outlet, see detail) Orenco Systems®, Inc. Copyright © 2011 <u>(L</u>) (see detail) Discharge/" = 2'-0"-VeriComm® Control Panel Discharge ç

Title:

NDW-ATX-RT-STD-17

Rev: **A-05**

Date: 9/08/2011